

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
10 February 2005 (10.02.2005)


PCT

(10) International Publication Number  
**WO 2005/012774 A1**

- (51) International Patent Classification<sup>7</sup>: **F16K 1/12**
- (21) International Application Number:  
PCT/GB2004/003213
- (22) International Filing Date: 26 July 2004 (26.07.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0317291.3 24 July 2003 (24.07.2003) GB
- (71) Applicant (for all designated States except US): **BW TECHNOLOGIES LTD** [GB/GB]; Abbey Business Park, Monks Walk, Farnham, Surrey GU9 8HT (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **GRANT, Jon** [GB/GB]; North Court, Court Manor, Croft Lane, Cron-dall, Farnham, Surrey GU10 5QF (GB).
- (74) Agent: **FRY, Alan, Valentine**; Fry Heath & Spence LLP, The Gables, Massetts Road, Horley, Surrey RH6 7DQ (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: VALVES FOR DRINKING VESSELS



(57) Abstract: A valve for selectively providing access to a supply of drinking fluid retained within a portable flexible container (18) comprises a tubular body (1) having at one end a stem (2) insertable into an opening in communication with the container and at its other end an outlet (3) through which fluid from the container can leave the valve. A piston (6) is mounted for sliding movement within a central bore (4) of the body and is resiliently urged into engagement with an annular seating (11) positioned at the bore end closest to the outlet (3). Means are provided for moving the piston (6) against the action of the resilient means (14) to enable fluid to be drawn from the container past the piston and through the outlet.



FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*